

**EXPANDABLE THERMOPLASTIC RESIN PARTICLE**

**Patent number:** JP3273036  
**Publication date:** 1991-12-04  
**Inventor:** IKEDA TOSHIKI; BEPPU YOSHIJI  
**Applicant:** SEKISUI PLASTICS  
**Classification:**  
- **international:** C08J9/224  
- **european:**  
**Application number:** JP19900073957 19900322  
**Priority number(s):** JP19900073957 19900322

[Report a data error here](#)**Abstract of JP3273036**

PURPOSE: To prevent agglomeration from occurring during pre-expansion, avoid fusion during molding from being hindered, and prevent exudation of water, a color, oil or fat, etc., to the surface of a foamed molding by coating the surface of an expandable thermoplastic resin particle with a cyclodextrin compsn. CONSTITUTION: The surface of an expandable thermoplastic resin particle comprising a thermoplastic resin particle contg. a blowing agent comprising a hydrocarbon having a b.p. lower than the m.p. of the particle is coated with a cyclodextrin compsn. As the compsn., a polymer obtd. by fixing at least one cyclodextrin selected from the group consisting of alpha-, beta-, and gamma-cyclodextrins to a copolymer can be used; the compsn. contg. at least 20wt.% cyclodextrin is pref.

---

Data supplied from the **esp@cenet** database - Worldwide